

ALTEA



CARATTERISTICHE TECNICHE / TECHNICAL CHARACTERISTIC

CALDAIA / BOILER: 3.5lt (1gr) - 14lt (2gr) - 21 lt (3gr)

RESISTENZA / HEATING ELEMENT: 2000W (1gr) - 4500W (2gr) - 6000W (3gr)

230V mono fase o 380V trifase / 230V in single-phase or 380V 3-phases

Pompa rotativa / Incorporated rotatory pump

Rubinetto vapore e acqua / Steam and hot water spray

Valvola antirisucchio / Antistuck-in valve

Livello acqua a vista / Boiler's level at sight

Carico automatico / Automatic boiler's loading

Auto livello / Self level control

Piedini regolabili / Height-adjustable foot

Disponibile nella versione gruppi alti / Also available in tall groups version

Colori/Colours	■ □ ■ ■	1 Groups	2 Groups	3 Groups
Larghezza/Width (mm)		500	700	900
Profondità/Depth (mm)		460	500	500
Altezza/Height (mm)		460	500	500
Peso/Weight (kg)		30	50	70
Potenza/Power (V)		230	380	380
Frequenza/Frequency (Hz)		50-60	50-60	50-60
Resistenza/Heating element (W)		2000	4500	6000
Caldaia/Boiler (L)		3.5	14	21